

The `l3pdf` module

Embedding and referencing files in a PDF

L^AT_EX PDF management testphase bundle

The L^AT_EX Project*

Version 0.96k, released 2024-09-02

1 `l3pdf` documentation

1.1 Introduction

1.1.1 Background

External files can be referenced from a PDF in three ways:

1. through an annotation of type Link,
2. by referencing a local file in the file system,
3. by embedding the file directly into the PDF

Case 1 (Links) are created with the `\pdfannot` commands. This module handles the two other cases. Actually from the view of the PDF format they are quite similar: Case 2 is case 3 without the stream object and without the `/EF` entry in the `/Filespec` dictionary (this points to the stream object of the file). Not embedding the file makes the PDF smaller. But it is also less portable: the files can only be found if they are in the right location relative to the PDF. The normal case is to embed the file.

The tasks to embed and reference such a file are

1. Embed the file in a stream.
2. Create a Filespec dictionary which references the stream object in the `/EF` dictionary:

```
<<
  /Type /Filespec
  /F (l3pdffile.dtx)
  /UF (l3pdffile.dtx)
  /AFRelationship /Source
  /EF <</F 21 0 R /UF 21 0 R>> %case 3, embedded file
>>
```

*E-mail: latex-team@latex-project.org

The file names in the `/UF` and `/F` value don't need to be identical to the name of file on the disc. It is quite possible to embed a `zzz.tex` and name it `blub.tex`. The second name is then what the user will see in the attachment list or in the properties of an annotation.

3. Reference the Filespec dictionary so that the user can access the file. This can be done in various way:

- (a) With an annotation (`/Subtype/FileAttachment`). This is done by `attachfile`, `attachfile2` and `intopdf`. Typical entries of such an annotation are:

key	value type	notes
<code>/FS</code>	object reference	(Filespec dictionary)
<code>/Name</code>	name	<code>/Graph</code> , <code>/PushPin</code> , <code>/Paperclip</code> , <code>/Tag</code>
<code>/Contents</code>	text string	optional but recommended
<code>/F</code>	integer	Flags
<code>/AP</code>	dictionary	Appearance (required if <code>rectangle > 0</code>)
<code>/AS</code>	name	

The `/AP` takes precedence over `Border` and similar keys.

- (b) Through an entry in the `/EmbeddedFiles` name tree. This is what `embedfiles` does.

```
20 0 obj %Document Name tree
  <</EmbeddedFiles 21 0 R>>
  endobj
  21 0 obj %Embedded Files Name dictionary
  <</Names [(AcmeCustomCrypto Protected PDF.pdf) 17 0 R]>>
  endobj
```

The strings (keys) in the `/Names` dictionary must be sorted lexically. But they don't have to be the file name or anything related to the file name. The resource management code uses `l3ef0001`, `l3ef0002` . . . , which allows up to 9999 files. The key can be needed to identify the start file in a collection, so their relation to the files are stored in a property list.

- (c) Through the `/AF` key in various objects (pdf 2.0). The value is normally an array of object references, but it can also be a name which is mapped to an array in `/Properties`:

```
/AF /NamedAF BDC
/Properties <</NamedAF [12 0 R]
```

The related `/Filespec` dictionary should contain an `/AFRelationship` key in this case (but it doesn't harm to add it by default anyway). The values of this key is describe in table 1.

1.1.2 Task 1: Embedding a file

Embedding an existing file is in most cases quite straightforward. This module offers commands, but it can also be done with the basic commands from the `l3pdf` module `\pdf_object_unnamed_write:nn` or `\pdf_object_new:n/\pdf_object_write:nnn` or primitive commands to create objects. The object number should be stored for the reference in the `/Filespec` dictionary.

Table 1: Values of the `/AFRelationship` key

Source	shall be used if this file specification is the original source material for the associated content.
Data	shall be used if this file specification represents information used to derive a visual presentation – such as for a table or a graph.
Alternative	shall be used if this file specification is an alternative representation of content, for example audio.
Supplement	shall be used if this file specification represents a supplemental representation of the original source or data that may be more easily consumable (e.g., A MathML version of an equation).
EncryptedPayload	shall be used if this file specification is an encrypted payload document that should be displayed to the user if the PDF processor has the cryptographic filter needed to decrypt the document.
FormData	shall be used if this file specification is the data associated with the AcroForm (see 12.7.3, “Interactive form dictionary”) of this PDF.
Schema	shall be used if this file specification is a schema definition for the associated object (e.g. an XML schema associated with a metadata stream).
Unspecified	(default value) shall be used when the relationship is not known or cannot be described using one of the other values.
Other names	Second-class names (see Annex E, “(normative) PDF Name Registry”) should be used to represent other types of relationships.

```

\pdf_object_unnamed_write:ne {fstream}
{
  {
    /Type /EmbeddedFile
    /Subtype /application\c_hash_str2Fpostscript
    /Params
    <<
      /ModDate ~ (\file_timestamp:n{example-image.eps})
      /Size ~ \file_size:n {example-image.eps}
      /Checksum ~ (\file_md5five_hash:n {example-image.eps})
    >>
  }
  {example-image.eps}
}
\tl_set:Ne \l_my_fileobj_tl {\pdf_object_ref_last:}

```

- The `/Params` dictionary is not always required, but the commands of these module will prefill them as shown in the examples. A `/CreationDate` entry has to be added explicitly as there is no sensible way to retrieve this automatically.
- The mimetype (in the `/Subtype`) should be properly escaped. This module contains a property list with maps a number of file extensions to mimetypes and the commands try to detect and fill the mimetype automatically.
- The dictionary can contain additional keys (`/Filter`, `/DecodeParms`), see the pdf reference.

1.1.3 Task 2: Creating the `/Filespec` dictionary

The `/Filespec` dictionary is a simple dictionary object, and can also be created in various ways. If it refers to an embedded file it should reference it in the `/EF` key.

1.1.4 Task 3: Referencing the `/Filespec` dictionary

Using the dictionary reference in annotations and `/AF` keys is unproblematic.



But to add it to the `/EmbeddedFiles` name tree so that it appears in the attachment panel requires special care: This name tree is a global resource and uncoordinated access can lead to clashes and files that are not visible or inaccessible. The access here is managed by the `l3pdfmanagement` module:

```

\pdfmanagement_add:nne{Catalog/Names}{EmbeddedFiles}{\objref}

```

1.2 Commands and tools of these module

`file`
`file/Params`
`file/streamParams`
`file/Filespec`

The module predefines and uses a number of local dictionaries for the components of the stream and the `/Filespec` object. These dictionaries are then used by the `\pdffile_embed_XX`. The content of these dictionaries can be changed by users with the commands from the `l3pdfdict` module, but it should be done only locally to avoid side effects on uses by other packages/commands.

The preset values of these dictionaries are shown in table 2.

Table 2: Preset values in the file dictionaries

dictionary	key	value
<code>l_pdffile</code>	Type	/EmbeddedFile
<code>l_pdffile/Params</code>	Size	<code>\file_size:n{\l_pdffile_source_name_str}</code>
<code>l_pdffile/Params</code>	ModDate	<code>(\file_timestamp:n {\l_pdffile_source_name_str})</code>
<code>l_pdffile/Params</code>	Checksum	<code>(\file_md5five_hash:n{\l_pdffile_source_name_str})</code>
<code>l_pdffile/streamParams</code>		a /ModDate entry with year/month/date (used with <code>\pdffile_embed_stream:nnn</code>)
<code>l_pdffile/Filespec</code>	Type	/Filespec
<code>l_pdffile/Filespec</code>	AFRelationship	Unspecified

```
\pdffile_embed_file:nnn \pdffile_embed_file:nnn {<source filename>} {<target filename>} {<object name >}
```

This command embeds the file `<source filename>` in the PDF, and creates a /Filespec dictionary object named `<object name>`. The object name must be unique, it should start with the module name, so e.g. `module/name`. The command uses the content of the local dictionaries `l_pdffile`, `l_pdffile/Params` and `l_pdffile/Filespec` to setup the dictionary entries of the stream object and the /Filespec dictionary. The /F and /UF entry are filled with `<target filename>`.

It is an error if both `<target filename>` and `<source filename>` are empty.

If `<target filename>` is empty `<source filename>` is used instead.

If `<source filename>` is empty, only a /Filespec dictionary is created.

If the `l_pdffile` dictionary doesn't contain a Subtype entry with the mimetype, the command tries to guess it from the file extension of `<source filename>`. Unknown file extensions can be added (or known extension be changed) by adding to or changing the value in the property `\g_pdffile_mimetypes_prop`, see below.

When using `dvips` and `pstopdf` the actual embedding is done by `pstopdf`. `pstopdf` will embed files only if used with the option `-dNOSAFER` and will not be able to use files which are found with `kpathsea`.

`<target filename>` doesn't need to be a file name with an extension, but it is recommended as security settings in the pdf viewer can restrict access to known file types.

```
\pdffile_embed_stream:nnn \pdffile_embed_stream:nnn {<content>} {<target filename>} {<object name>}
\pdffile_embed_stream:nnN \pdffile_embed_stream:nnN {<content>} {<target filename>} {<tl var>}
```

This command embeds the `<content>` in the PDF in a stream objects and creates either a /Filespec dictionary object named `<object name>`, or stores the object reference (what you would get with `\pdf_object_ref:n` in `<tl var>`). `<content>` is wrapped in a `\exp_not:n`. The object name must be unique. The command uses the content of the local dictionaries `l_pdffile`, `l_pdffile/streamParams` and `l_pdffile/Filespec` to setup the dictionary entries of the stream object and the /Filespec dictionary. The /F and /UF entry are filled with `<target filename>`. If `<target filename>` is empty the fix name `stream.txt` is used instead.

If the `l_pdffile` dictionary doesn't contain a Subtype entry with the mimetype, the command tries to guess it from the file extension of `<target filename>`.

`<target filename>` doesn't need to be a file name with an extension, but it is recommended as security settings in the pdf viewer can restrict access to known file types.

The stream should not be too long, at least PS imposes a size limit for strings.

`\pdffile_filespec:nnn` `\pdffile_filespec:nnn` `{<object name>}{<file name>}`stream object reference

`\pdffile_filespec:nne`

The previous commands are fine if stream and filespec dictionary can be created together. But there are cases where the `filespec` dictionary should be referenced when the stream object doesn't exist yet. For example in the `AF` key of a structure at the begin of an environment where the stream is created from the body.

This command allows to write a filespec dictionary alone and reference a previously created stream.

```
\pdf_object_new:n {module/filespec/A} % a new filespec object
\pdf_object_ref:n {module/filespec/A} % a reference
\pdf_object_unnamed_write:nn { stream }{ {...}{content} } %writing the stream
% filling and writing the filespec dictionary:
\pdffile_filespec:nnn {module/filespec/A}{A.xml}{\pdf_object_ref_last:}
```

`\g_pdffile_mimetypes_prop` This property contains a list of extensions and their mimetypes. Values can be added or changed with the standard commands:

```
\prop_gput:Nnn \g_pdffile_mimetypes_prop {.abc}{text/plain}
```

The extension should start with a period, the mimetype should be given as plain text (it will be escaped internally). Extensions with two periods are not supported.

`\l_pdffile_source_name_str` This variable is set at the begin of `\pdffile_embed_file:nnn`. It can be (and is) used in the file dictionaries, see table 2 for examples.

`\g_pdffile_embed_prop` This property holds a list of embedded files. It is used by the following show command. The keys are the object names, the argument holds a key word, the source file name and the target file name.

`\pdffile_embed_show:` This shows the embedded files with their source and target name.

1.3 Example

```
\group_begin:
%set the relationship:
\pdfdict_put:nnn {l_pdffile/Filespec} {AFRelationship}{/Source}
%set the description key. The text must first be converted:
\pdf_string_from_unicode:nnN {utf16/string}
  {this~is~an~odd~description~with~öäü}
  \l_tmpa_str
\pdfdict_put:nne {l_pdffile/Filespec} {Desc}{\l_tmpa_str}
%embeds testinput.txt and calls it grüße.txt
\pdffile_embed_file:nnn {testinput.txt}{grüße.txt}{mymodule/example1}
%reference it in the panel
\pdfmanagement_add:nne
  {Catalog/Names}
```

```

{EmbeddedFiles}
{\pdf_object_ref:n{mymodule/example1}}
\group_end:

```

2 l3pdffile implementation

```

1 <*header>
2 \ProvidesExplPackage{l3pdffile}{2024-09-02}{0.96k}
3 {embedding and referencing files in PDF---LaTeX PDF management testphase bundle}
4 \RequirePackage{l3pdfptools} %temporarily!!
5 </header>
6 <*package>
7 <@@=pdffile>
8 \cs_new_protected:Npn \__pdffile_filename_convert_to_print:nN #1 #2
9 {\pdf_string_from_unicode:nnN {utf16/hex}{#1}{#2}}

```

2.1 Messages

```

10 \msg_new:nnn { pdffile } { file-not-found }
11 {
12   File~'\tl_to_str:n{#1}'~not~found
13 }
14
15 \msg_new:nnn { pdffile } { mimetype-missing }
16 {
17   Mime~type~not~set~for~file~'\tl_to_str:n{#1}'
18 }
19
20 \msg_new:nnn { pdffile } { target-name-missing }
21 {
22   a~target~name~for~the~/Filespec~dictionary~is~missing.
23 }
24
25 \msg_new:nnn { pdffile } { object-exists }
26 {
27   object~name~'#1'~is~already~used.
28 }
29
30 \msg_new:nnn { pdffile } { show-files }
31 {
32   The~following~files~have~been~embedded\\
33   #1
34 }

```

\l__pdffile_tmpa_tl temporary variables: generic, for extension, subtype, to store the ref.

\l__pdffile_tmpb_tl

\g__pdffile_tmpa_tl

(End of definition for \l__pdffile_tmpa_tl and others.)

\l__pdffile_tmpa_str 35 \tl_new:N \l__pdffile_tmpa_tl

\l__pdffile_tmpb_str 36 \tl_new:N \l__pdffile_tmpb_tl

\l__pdffile_ext_str 37 \tl_new:N \g__pdffile_tmpa_tl

\l__pdffile_automimetype_tl 38 \str_new:N \l__pdffile_tmpa_str

\l__pdffile_embed_ref_tl 39 \str_new:N \l__pdffile_tmpb_str

40 \str_new:N \l__pdffile_ext_str

41 \tl_new:N \l__pdffile_automimetype_tl

```
42 \tl_new:N \l__pdffile_embed_ref_tl
```

`\g_pdffile_mimetypes_prop` This variable holds common mimetypes. The key is an extension with (one) period, the value the description, e.g. `text/csv`.

(End of definition for `\g_pdffile_mimetypes_prop`. This variable is documented on page 6.)

```
43 \prop_new:N \g_pdffile_mimetypes_prop
44 \prop_gset_from_keyval:Nn \g_pdffile_mimetypes_prop
45 {
46   ,.css = text/css
47   ,.csv = text/csv
48   ,.html= text/html
49   ,.dtx = text/plain %or application/x-tex, not in iana.org list
50   ,.eps = application/postscript
51   ,.jpg = image/jpeg
52   ,.mp4 = video/mp4
53   ,.pdf = application/pdf
54   ,.png = image/png
55   ,.tex = application/x-tex %not in iana.org list but probably better
56   ,.txt = text/plain
57   ,.sty = text/plain
58   ,.xml = application/xml
59 }
```

`\l_pdffile_source_name_str` `\l_pdffile_source_name_str` will be set at the begin of the command and contains the full file name and can be used e.g. with `\file_timestamp:n`.

(End of definition for `\l_pdffile_source_name_str`. This variable is documented on page 6.)

```
60 \str_new:N \l_pdffile_source_name_str
```

Here we define and setup the local dictionaries. We add a `ModDate` to ensure that there is an entry if associated files are used.

```
61 \pdfdict_new:n { l_pdffile }
62 \pdfdict_put:nnn { l_pdffile }{Type}{/EmbeddedFile}
63 \pdfdict_new:n { l_pdffile/Params }
64 \pdfdict_put:nnn { l_pdffile/Params }
65   {ModDate} { (\file_timestamp:n { \l_pdffile_source_name_str }) }
66 \pdfdict_put:nnn { l_pdffile/Params }
67   {Size} { \file_size:n { \l_pdffile_source_name_str } }
68 \pdfdict_put:nnn { l_pdffile/Params }
69   {Checksum} { (\file_md5_hash:n { \l_pdffile_source_name_str }) }
70 \pdfdict_new:n { l_pdffile/streamParams }
71 \pdfdict_put:nnn { l_pdffile/streamParams }
72   {ModDate} {
73     (
74       D:\int_use:N\c_sys_year_int
75       \int_compare:nNnT{\c_sys_month_int}<{10}{0}
76       \int_use:N\c_sys_month_int
77       \int_compare:nNnT{\c_sys_day_int}<{10}{0}
78       \int_use:N\c_sys_day_int
79     )
80   }
81 \pdfdict_new:n { l_pdffile/Filespec }
82 \pdfdict_put:nnn { l_pdffile/Filespec }
```



```

83 {Type} { /Filespec }
84 \pdfdict_put:nnn { l_pdffile/Filespec }
85 {AFRelationship} { /Unspecified }
86

```

`\g_pdffile_embed_prop` we record here the relation
 $\langle \text{object name} \rangle \Rightarrow \{ \langle \text{file/stream or empty} \rangle \} \{ \langle \text{sourcename} \rangle \} \{ \langle \text{targetname} \rangle \}$

```

87 \prop_new:N \g_pdffile_embed_prop

```

(End of definition for `\g_pdffile_embed_prop`. This variable is documented on page 6.)

```

\pdffile_embed_show:
88 \cs_new_protected:Npn \pdffile_embed_show:
89 {
90   \msg_show:nne
91     {pdffile}{show-files}
92     {
93       \prop_map_function:NN {\g_pdffile_embed_prop} \msg_show_item:nn
94     }
95 }

```

(End of definition for `\pdffile_embed_show:`. This function is documented on page 6.)

`\pdffile_embed_file:nnn` At first a command to set the mimetype. It either uses the current value in the file
`\pdffile_embed_stream:nnn` dictionary, or tries to guess it from the extension.
`\pdffile_embed_stream:nnN`

```

96 % #1 file name,
97 % #2 tl to return the (printed) value for the guessed mimetype
98 \cs_new_protected:Npn \__pdffile_mimetype_set:nN #1 #2
99 {
100   \file_parse_full_name:nNNN
101     {#1}
102     \l__pdffile_tmpa_str %unused
103     \l__pdffile_tmpb_str %unused
104     \l__pdffile_ext_str
105   %check if Subtype has been set
106   \pdfdict_get:nnN { l_pdffile } {Subtype} \l__pdffile_tmpa_tl
107   %if not look up in the prop:
108   \quark_if_no_value:NT \l__pdffile_tmpa_tl
109   {
110     \prop_get:NVNTF
111       \g_pdffile_mimetypes_prop
112       \l__pdffile_ext_str
113       \l__pdffile_tmpb_tl
114     {
115       \tl_set:Nc #2 { /Subtype-\pdf_name_from_unicode_e:V \l__pdffile_tmpb_tl }
116     }
117     {
118       \msg_warning:nne { pdffile } { mimetype-missing } {#1}
119       \tl_clear:N #2
120     }
121   }
122 }

```

```

123
124 \cs_generate_variant:Nn \__pdffile_mimetype_set:nN {VN}
125
126 % #1 file name,
127 % #2 tl, should be empty or contain /Subtype /mimetype
128 % e.g. result from \__pdffile_mimetype_set:NN
129 \cs_new_protected:Npn \__pdffile_fstream_write:nN #1 #2
130 {
131   \pdf_object_unnamed_write:ne { fstream }
132   {
133     {
134       #2
135       \pdfdict_use:n { l_pdffile}
136       \pdfdict_if_empty:nF { l_pdffile/Params}
137       {
138         /Params
139         <<
140         \pdfdict_use:n { l_pdffile/Params}
141         >>
142       }
143     }
144     { #1 }
145   }
146   \tl_clear:N \l__pdffile_automimetype_tl
147 }
148
149 \cs_generate_variant:Nn \__pdffile_fstream_write:nN {VN}
150
151 % #1 file content
152 % #2 tl, should be empty or contain /Subtype /mimtype
153 % e.g. result from \__pdffile_mimetype_set:NN
154 \cs_new_protected:Npn \__pdffile_stream_write:nN #1 #2
155 {
156   \pdf_object_unnamed_write:ne { stream }
157   {
158     {
159       #2
160       \pdfdict_use:n { l_pdffile}
161       \pdfdict_if_empty:nF { l_pdffile/streamParams}
162       {
163         /Params
164         <<
165         \pdfdict_use:n { l_pdffile/streamParams}
166         >>
167       }
168     }
169     { \exp_not:n { #1 } }
170   }
171   \tl_clear:N \l__pdffile_automimetype_tl
172 }
173
174 \cs_generate_variant:Nn \__pdffile_stream_write:nN {VN}
175
176 % #1 symbolic name of dict object

```

```

177 % #2 target file name,
178 % #3 object ref of the file stream.
179 \cs_new_protected:Npn \__pdffile_filespec_write:nnn #1 #2 #3
180 {
181   \tl_if_blank:nTF { #2 }
182   {
183     \msg_error:nn {pdffile}{target-name-missing}
184   }
185   {
186     \group_begin:
187     \pdf_string_from_unicode:nnN {utf8/string}{#2}\l__pdffile_tmpa_str
188     \pdfdict_put:nne {l_pdffile/Filespec}{F} { \l__pdffile_tmpa_str }
189     \__pdffile_filename_convert_to_print:nN { #2 } \l__pdffile_tmpa_str
190     \pdfdict_put:nne {l_pdffile/Filespec}{UF}{ \l__pdffile_tmpa_str }
191     \pdf_object_write:nne { #1 } { dict }
192     {
193       \pdfdict_use:n { l_pdffile/Filespec}
194       \tl_if_empty:nF { #3 }
195       {
196         /EF <</F~#3 /UF~#3>>
197       }
198     }
199     \group_end:
200   }
201 }
202
203 % #1 target file name #2 object ref of file stream #3 reference of object
204 \cs_new_protected:Npn \__pdffile_filespec_write:nnN #1 #2 #3
205 {
206   \tl_if_blank:nTF { #1 }
207   {
208     \msg_error:nn {pdffile}{target-name-missing}
209   }
210   {
211     \group_begin:
212     \pdf_string_from_unicode:nnN {utf8/string}{#1}\l__pdffile_tmpa_str
213     \pdfdict_put:nne {l_pdffile/Filespec}{F} { \l__pdffile_tmpa_str }
214     \__pdffile_filename_convert_to_print:nN { #1 } \l__pdffile_tmpa_str
215     \pdfdict_put:nne {l_pdffile/Filespec}{UF}{ \l__pdffile_tmpa_str }
216     \pdf_object_unnamed_write:ne {dict}
217     {
218       \pdfdict_use:n { l_pdffile/Filespec}
219       \tl_if_empty:nF { #2 }
220       {
221         /EF <</F~#2 /UF~#2>>
222       }
223     }
224     \tl_gset:Ne\g__pdffile_tmpa_tl{\pdf_object_ref_last:}
225     \group_end:
226     \tl_set_eq:NN#3\g__pdffile_tmpa_tl
227   }
228 }
229
230 \cs_set_eq:NN \pdffile_filespec:nnn \__pdffile_filespec_write:nnn

```

```

231 \cs_generate_variant:Nn \pdffile_filespec:nnn {nne,nnx}
232 % #1 {source filename}
233 % #2 {target filename}
234 % #3 { filespec object name } (will internally get a prefix! ??)
235 \cs_new_protected:Npn \pdffile_embed_file:nnn #1 #2 #3
236 { %           if #1 empty => only filespec
237   %           if #2 empty => = #1
238   \pdf_object_if_exist:nTF { #3 }
239   {
240     \msg_error:nnn { pdffile }{ object-exists } { #3 }
241   }
242   {
243     \tl_if_blank:nTF { #1 }
244     {
245       \tl_set:Nn \l__pdffile_embed_ref_tl {}
246     }
247     {
248       \file_get_full_name:nTF {#1} \l__pdffile_source_name_str
249       {
250         \__pdffile_mimetype_set:VN
251         \l__pdffile_source_name_str
252         \l__pdffile_automimetype_tl
253         \__pdffile_fstream_write:VN
254         \l__pdffile_source_name_str
255         \l__pdffile_automimetype_tl
256         \tl_set:Ne \l__pdffile_embed_ref_tl { \pdf_object_ref_last: }
257       }
258       {
259         \msg_error:nnn { pdffile }{ file-not-found }{ #1 }
260       }
261     }
262   }
263   \prop_gput:Nne
264     \g_pdffile_embed_prop
265     { #3 }
266     {
267       { \tl_if_blank:nTF { #1 } {filespec}{file} }
268       { \l__pdffile_source_name_str }
269       {
270         \tl_if_blank:nTF { #2 }
271         { \l__pdffile_source_name_str }
272         { \tl_to_str:n{#2} }
273       }
274     }
275   \tl_if_blank:nTF { #2 }
276   {
277     \pdf_object_new:n { #3 }
278     \exp_args:Nnne
279       \__pdffile_filespec_write:nnn
280       % #1 dict, #2 target file name, #3 object ref
281       { #3 }
282       { #1 }
283       { \l__pdffile_embed_ref_tl }
284   }

```

```

285     {
286     \pdf_object_new:n { #3 }
287     \exp_args:Nnne
288     \__pdffile_filespec_write:nnn
289     %#1 dict, #2 target file name, #3 object ref
290     { #3 }
291     { #2 }
292     {\l__pdffile_embed_ref_tl}
293     }
294   }
295 }
296
297
298 % #1{stream content}
299 % #2{target filename}
300 % #3{file object name }
301 \cs_new_protected:Npn \pdffile_embed_stream:nnn #1 #2 #3
302 {
303   % if #2 empty => error
304   \pdf_object_if_exist:nTF { #3 }
305   {
306     \msg_error:nnn { pdffile }{ object-exists } { #3 }
307   }
308   {
309     \prop_gput:Nne
310     \g_pdffile_embed_prop
311     { #3 }
312     {{stream}}{\t1_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}}}}
313     \t1_if_blank:nTF {#2}
314     { \__pdffile_mimetype_set:nN {stream.txt}\l__pdffile_automimetype_tl}
315     { \__pdffile_mimetype_set:nN { #2 } \l__pdffile_automimetype_tl }
316     \__pdffile_stream_write:nN
317     { #1 }
318     \l__pdffile_automimetype_tl
319     \t1_set:Ne \l__pdffile_embed_ref_tl { \pdf_object_ref_last: }
320     \pdf_object_new:n { #3 }
321     \exp_args:Nnee
322     \__pdffile_filespec_write:nnn
323     %#1 dict, #2 target file name, #3 object ref
324     { #3 }
325     { \t1_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}} }
326     {\l__pdffile_embed_ref_tl}
327   }
328 }
329
330 \cs_new_protected:Npn \pdffile_embed_stream:nnN #1 #2 #3
331 {
332   \t1_if_blank:nTF {#2}
333   { \__pdffile_mimetype_set:nN {stream.txt}\l__pdffile_automimetype_tl}
334   { \__pdffile_mimetype_set:nN { #2 } \l__pdffile_automimetype_tl }
335   \__pdffile_stream_write:nN
336   { #1 }
337   \l__pdffile_automimetype_tl
338   \t1_set:Ne \l__pdffile_embed_ref_tl { \pdf_object_ref_last: }

```

```

339     \exp_args:Nee
340     \__pdffile_filespec_write:nnN
341     % #1 target file name, #2 object ref of stream, #3 object ref of filespec
342     { \tl_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}} }
343     {\l__pdffile_embed_ref_tl}
344     #3
345     \prop_gput:Nee
346     \g_pdffile_embed_prop
347     { #3 }
348     {\stream}{\tl_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}}}}
349   }
350
351
352 </package>

```

(End of definition for `\pdffile_embed_file:nnn` and others. These functions are documented on page 5.)

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

	Symbols		
<code>\</code>	32	
	pdffile commands:		
	<code>_pdffile_filespec:nnn</code>	6
	C		
	cs commands:		
	<code>\cs_generate_variant:Nn</code>	
		124, 149, 174, 231
	<code>\cs_new_protected:Npn</code>	8,
			88, 98, 129, 154, 179, 204, 235, 301, 330
	<code>\cs_set_eq:NN</code>	230
	E		
	exp commands:		
	<code>\exp_args:Nee</code>	339
	<code>\exp_args:Nnee</code>	321
	<code>\exp_args:Nnne</code>	278, 287
	<code>\exp_not:n</code>	..	5, 169, 312, 325, 342, 348
	F		
	file	4
	file commands:		
	<code>\file_get_full_name:nNTF</code>	248
	<code>\file_md5_hash:n</code>	69
	<code>\file_parse_full_name:nNNN</code>	100
	<code>\file_size:n</code>	67
	<code>\file_timestamp:n</code>	8, 65
	<code>file/Filespec</code>	4
	<code>file/Params</code>	4
	<code>file/streamParams</code>	4
	G		
	group commands:		
	<code>\group_begin:</code>	186, 211
	<code>\group_end:</code>	199, 225
	I		
	int commands:		
	<code>\int_compare:nNnTF</code>	75, 77
	<code>\int_use:N</code>	74, 76, 78
	M		
	msg commands:		
	<code>\msg_error:nn</code>	183, 208
	<code>\msg_error:nnn</code>	240, 259, 306
	<code>\msg_new:nnn</code>	10, 15, 20, 25, 30
	<code>\msg_show:nnn</code>	90
	<code>\msg_show_item:nn</code>	93
	<code>\msg_warning:nnn</code>	118
	P		
	pdf commands:		
	<code>\pdf_name_from_unicode_e:n</code>	115
	<code>\pdf_object_if_exist:nTF</code>	...	238, 304
	<code>\pdf_object_new:n</code>	...	2, 277, 286, 320

\pdf_object_ref:n	5	__pdffile_mimetype_set:NN	128, 153
\pdf_object_ref_last:		__pdffile_mimetype_set:nN	96, 98, 124, 250, 314, 315, 333, 334
.....	224, 256, 319, 338	__pdffile_stream_write:nN	96, 154, 174, 316, 335
\pdf_object_unnamed_write:nn	2, 131, 156, 216	\l__pdffile_tmpa_str	35, 38, 102, 187, 188, 189, 190, 212, 213, 214, 215
\pdf_object_write:nnn	2, 191	\g__pdffile_tmpa_tl	35, 37, 224, 226
\pdf_string_from_unicode:nnN	9, 187, 212	\l__pdffile_tmpa_tl	35, 35, 106, 108
\pdfannot	1	\l__pdffile_tmpb_str	35, 39, 103
pdfdict commands:		\l__pdffile_tmpb_tl	35, 36, 113, 115
\pdfdict_get:nnN	106	prop commands:	
\pdfdict_if_empty:nTF	136, 161	\prop_get:NnNTF	110
\pdfdict_new:n	61, 63, 70, 81	\prop_gput:Nnn	263, 309, 345
\pdfdict_put:nnn	62, 64, 66, 68, 71, 82, 84, 188, 190, 213, 215	\prop_gset_from_keyval:Nn	44
\pdfdict_use:n	135, 140, 160, 165, 193, 218	\prop_map_function:NN	93
pdffile commands:		\prop_new:N	43, 87
\pdffile_embed_file:nnn	5, 6, 96, 235	\ProvidesExplPackage	2
\g_pdffile_embed_prop	6, 87, 93, 264, 310, 346		
\pdffile_embed_show:	6, 88, 88	Q	
\pdffile_embed_stream:nnN	5, 96, 330	quark commands:	
\pdffile_embed_stream:nnn	5, 96, 301	\quark_if_no_value:NnTF	108
\pdffile_embed_XX	4		
\pdffile_filespec:nnn	6, 230, 231	R	
\g_pdffile_mimetypes_prop	5, 6, 43, 43, 44, 111	\RequirePackage	4
\l__pdffile_source_name_str	6, 8, 60, 60, 65, 67, 69, 248, 251, 254, 268, 271		
pdffile internal commands:		S	
\l__pdffile_automimetype_tl	35, 41, 146, 171, 252, 255, 314, 315, 318, 333, 334, 337	str commands:	
\l__pdffile_embed_ref_tl	35, 42, 245, 256, 283, 292, 319, 326, 338, 343	\str_new:N	38, 39, 40, 60
\l__pdffile_ext_str	35, 40, 104, 112	sys commands:	
__pdffile_filename_convert_to_print:nN	8, 189, 214	\c_sys_day_int	77, 78
__pdffile_filespec_write:nnN	204, 340	\c_sys_month_int	75, 76
__pdffile_filespec_write:nnn	179, 230, 279, 288, 322	\c_sys_year_int	74
__pdffile_fstream_write:nN	96, 129, 149, 253		
		T	
		tl commands:	
		\tl_clear:N	119, 146, 171
		\tl_gset:Nn	224
		\tl_if_blank:nTF	181, 206, 243, 267, 270, 275, 312, 313, 325, 332, 342, 348
		\tl_if_empty:nTF	194, 219
		\tl_new:N	35, 36, 37, 41, 42
		\tl_set:Nn	115, 245, 256, 319, 338
		\tl_set_eq:NN	226
		\tl_to_str:n	12, 17, 272